












TECHNICAL CHARACTERISTICS

wineo 400 wineo

Heterogeneous resilient-flooring to glue - Covering type according to EN ISO 10582




	wineo 400 wood	wineo 400 wood XL	wineo 400 stone	
Format	1200 x 180 mm	1505 x 235 mm	609.6 x 304.8 mm	
Product thickness	2 mm	2 mm	2 mm	
Planks, tiles / m² per box	18 / 3.89 m ²	12 / 4.24 m ²	18 / 3.34 m ²	
Boxes / m² per pallet	60 / 233.40 m ²	64 / 271.36 m ²	60 / 200.40 m ²	
Guarantee	15 years for private use according to Windmüller warranty conditions – www.wineo.de			

Classification			Product composition	
	Utilization class 23 EN ISO 10874	Heavy-duty use in the domestic area	1	Surface sealing
	Utilization class 31 EN ISO 10874	Medium use in the commercial sector	2	Surface texture Various embossings
	Wear layer binder content EN ISO 10582	Type I	3	Wear layer Thickness 0.3 mm
	R9 Anti slip category DIN 51130	R 9	4	Decor Decor film
	Staining and chemical resistance EN ISO 26987	Good resistance according to the concentration and residence time	5	Base layer
	Light fastness EN ISO 105-B02	Light fastness (method 2) ≥ 6	6	Backing
	Residual indentation EN ISO 24343-1	≤ 0.1 mm without insulation mat ~ 0.17 mm with insulation mat silentPREMIUM		DESIGN Flooring to glue 
	Thermal resistance EN 12667	0.011 (m ² K)/W without insulation mat 0.021 (m ² K)/W with insulation mat silentPREMIUM		wood – bevelled edge - 4-sides wood XL – registered embossed surface, bevelled edge – 4-sides
	Impact sound reduction EN ISO 16251-1	~ 4 dB		
	Disposal	<u>Private:</u> Possible with normal domestic refuse <u>Commercial:</u> Refuse-key-no. AVV 170203		

CE - 18 -


Windmüller GmbH
Nord-West-Ring 21
D-32832 Augustdorf

DOP: 0301010
EN 14041:2004 / AC2006
1658

www.wineo.de

ÉMISSIONS DANS L'AIR INTÉRIEUR*



Information representative des émissions dans l'air intérieur des substances volatiles présentant un risque de toxicité par inhalation, sur une échelle de classe allant de C (fortes émissions) à A+ (très faibles émissions)

TÜV PROFIT CERT
70 710 4061-6
www.profitcert.com

tested for emissions, harmful substances

PREMIUM

factory made coated

Phthalat frei 100%

Relevant information:

- Underfloor heating: Suitable for all conventional hot water underfloor heating and electrical systems regulated up to a surface temperature of 27° C.
- Cleaning and care: see separate cleaning & care instruction.
- Technical subjects can be changed by Windmüller GmbH.